


TECHNICAL INFORMATION

Range :	Suction cup
Category :	Plates
Series :	7SB
Height (in mm) :	8.5
Shape :	Plate
Contact lip diameter :	15 mm
inner barrel diameter :	4.8 mm
Number of bellows :	0.5 Bellows
Horizontal force :	7.5 N
Vertical force :	3.5 N
Arrow :	1.5 mm



Variants:



- Variant reference:
7SB 15SLT A
- Color: Translucent
 - CE food certified
 - Matter: Silicone
 - Shore Hardness: SH60



- Variant reference:
7SB 15TPUB A
- Color: Blue
 - Matter: Thermoplastic
 - Shore Hardness: SH70



- Variant reference:
7SB 15NI A
- Color: Black
 - Matter: Nitrile
 - Shore Hardness: SH50

Material guide:

	Material	Code	Temperature resistance (°C)	Flexibility	Abrasion resistance	UV/Weather resistance	Oil resistance	Food compatibility	Migration test
	Silicone Translucent (Shore SH60)	SL T	-60/+250	✓✓✓✓	✓	✓✓✓✓	✓	FDA ** ✗	✗
	Thermoplastic Blue (Shore SH70)	TPUB	-20/+80	✓	✓✓✓✓	✓	✓✓✓	✗	✗
	Nitrile Black (Shore SH50)	NI	-10/+80	✓	✓	✗	✓✓✓	✗	✗

Requests for FDA and/or EC certificates must be made AT THE TIME OF ORDER. Any later request will incur additional charges. To meet the expectations of our industrial customers, NOVACOM offers the widest range of elastomer and thermoplastic materials. We can also develop new materials based on precise specifications, in order to solve specific applications for our customers.

✓✓✓✓ Excellent | ✓✓ Good | ✓ Low | ✗ Poor | ✗✗ Not recommended
 *FDA and/or EC certificate may be requested for various references at the time of order; please contact us.
 ** Food contact certification: (EC) 1935/2004 - (FDA) 21 CFR 177.2600
 *** Food contact certification: (EC) 10/2011 - (FDA) 21 CFR

Related products:



Adaptor - Female 1/8G - Female M5

Product reference: ADA G1/8F M5F



Adaptor - Male 1/8G - Female M5

Product reference: ADA G1/8M M5F
 E-mail: info@novacom-grp.com



Screw M5 - Head Ø 8 mm - L 9 mm

Product reference: SCR 15 M5M