


TECHNICAL INFORMATION

Range :	Suction cup
Category :	Plates
Series :	PFTM
Height (in mm) :	15
Shape :	Plate
Contact lip diameter :	8.6 mm
inner barrel diameter :	M5
Number of bellows :	0.5 Bellows
Horizontal force :	2.6 N
Vertical force :	1.3 N
Arrow :	1.2 mm



Variants:



Variant reference:

PFTM 8ANI M5M

- Color: Black
- Matter: Nitrile
- Shore Hardness: SH50



Variant reference:

PFTM 8ASLT M5M

- Color: Translucent
- CE food certified
- Matter: Silicone
- Shore Hardness: SH60



Variant reference:

PFTM 8AMNT M5M

- Color: Bordeaux
- Matter: Non-staining material
- Shore Hardness: SH60

Material guide:

	Material	Code	Temperature resistance (°C)	Flexibility	Abrasion resistance	UV/Weather resistance	Oil resistance	Food compatibility	Migration test
	Nitrile Black (Shore SH50)	NI	-10/+80	✓	✓	✗	✓✓	✗	✗
	Silicone Translucent (Shore SH60)	SL T	-60/+250	✓✓✓	✓	✓✓✓	✓	FDA  **	✗
	Non-staining material Bordeaux (Shore SH60)	MNT	-20/+160	✓	✓	✓✓✓	✓✓✓	✗	✗

Requests for FDA and/or EC certificates must be made AT THE TIME OF ORDER. Any later request will incur additional charges. To meet the expectations of our industrial customers, NOVACOM offers the widest range of elastomer and thermoplastic materials. We can also develop new materials based on precise specifications, in order to solve specific applications for our customers.



Excellent |



Good |



Low |



Poor |




Not recommended

*FDA and/or EC certificate may be requested for various references at the time of order; please contact us.

** Food contact certification: (EC) 1935/2004 - (FDA) 21 CFR 177.2600

*** Food contact certification: (EC) 10/2011 - (FDA) 21 CFR

Related products:



Flat suction cup series PFG Ø 5.3 mm

Product reference: PFG 05A-- A



Separable Male Fitting M5

Product reference: FTM 5A M5

E-mail: info@nova.com-grip.com

Z.A. de Sars et Rosières - 30, rue de l'épau - 59230 ROSULT - France

Phone. : +33 (0)3 27 30 53 53

VAT Number : FR57 381 120 484