


TECHNICAL INFORMATION

Range :	Suction cup
Category :	With bellows
Series :	PBG
Height (in mm) :	40.6
Shape :	1.5 Bellows
Contact lip diameter :	77.5 mm
Top diameter :	Female G1/4"
inner barrel diameter :	Female G1/4"
Number of bellows :	1.5 Bellows
Horizontal force :	197.5 N
Vertical force :	99 N
Arrow :	22 mm



Variants:



Variant reference:

PBG 75NI F14

- Color: Black
- Matter: Nitrile
- Shore Hardness: SH50



Variant reference:

PBG 75SLT F14

- Color: Translucent
- CE food certified
- Matter: Silicone
- Shore Hardness: SH60


Material guide:

	Material	Code	Temperature resistance (°C)	Flexibility	Abrasion resistance	UV/Weather resistance	Oil resistance	Food compatibility	Migration test
	Nitrile Black (Shore SH50)	NI	-10/+80	✓	✓	✗	✓✓	✗	✗
	Silicone Translucent (Shore SH60)	SL T	-60/+250	✓✓✓	✓	✓✓✓	✓	FDA  **	✗

Requests for FDA and/or EC certificates must be made AT THE TIME OF ORDER. Any later request will incur additional charges. To meet the expectations of our industrial customers, NOVACOM offers the widest range of elastomer and thermoplastic materials. We can also develop new materials based on precise specifications, in order to solve specific applications for our customers.

 Excellent |
  Good |
  Low |
  Poor |
  Not recommended
 *FDA and/or EC certificate may be requested for various references at the time of order; please contact us.
 ** Food contact certification: (EC) 1935/2004 - (FDA) 21 CFR 177.2600
 *** Food contact certification: (EC) 10/2011 - (FDA) 21 CFR

Related products:



Separable Female Fitting 1/4G

Product reference: FTF 60 G1/4



Separable Male Fitting 1/4G

Product reference: FTM 60 G1/4