


TECHNICAL INFORMATION

Range :	Suction cup
Category :	Plates
Series :	7
Height (in mm) :	16
Shape :	Plate
Contact lip diameter :	40 mm
inner barrel diameter :	11 mm
Number of bellows :	0.5 Bellows
Horizontal force :	57 N
Vertical force :	28.5 N
Arrow :	11 mm




Variants:



Variant reference:

71 40CN A

- Color: Brown FDA food certified
- Matter: Natural rubber
- Shore Hardness: SH40



Variant reference:

71 40NI A


- Color: Black
- Matter: Nitrile



Variant reference:

71 40SLT A

- Color: Translucent
- CE food certified
- Matter: Silicone
- Shore Hardness: SH60



Variant reference:

71 40NR A

- Color: Gray
- Matter: Natural rubber



Variant reference:

71 40SLB A

- Color: White
- FDA and CE food-grade certified
- Matter: Silicone
- Shore Hardness: SH40

Material guide:

	Material	Code	Temperature resistance (°C)	Flexibility	Abrasion resistance	UV/Weather resistance	Oil resistance	Food compatibility	Migration test
	Silicone Translucent (Shore SH60)	SL T	-60/+250	✓✓✓✓	✓	✓✓✓✓	✓	FDA ** ✗	✗
	Silicone White (Shore SH40)	SL B	-60/+250	✓✓✓✓	✗	✓✓✓✓	✗	FDA ** ✗	✗

Requests for FDA and/or EC certificates must be made AT THE TIME OF ORDER. Any later request will incur additional charges. To meet the expectations of our industrial customers, NOVACOM offers the widest range of elastomer and thermoplastic materials. We can also develop new materials based on precise specifications, in order to solve specific applications for our customers.


✓✓✓✓ Excellent | ✓✓ Good | ✓ Low | ✗ Poor | ✗✗ Not recommended

*FDA and/or EC certificate may be requested for various references at the time of order; please contact us.

** Food contact certification: (EC) 1935/2004 - (FDA) 21 CFR 177.2600

*** Food contact certification: (EC) 10/2011 - (FDA) 21 CFR

Related products:



Screw G1/4" - Head Ø 19 mm - L 24.5 mm

Product reference: M14T19L24.5