


TECHNICAL INFORMATION

Range :	Suction cup
Category :	With bellows
Series :	92
Height (in mm) :	31
Shape :	4.5 Bellows
Contact lip diameter :	20 mm
inner barrel diameter :	M5
Number of bellows :	4.5 Bellows
Horizontal force :	11.5 N
Vertical force :	6 N
Arrow :	13 mm



Variants:



Variant reference:

92 20NI M18

- Color: Black
- Matter: Nitrile
- Shore Hardness: SH70



Variant reference:

92 20SL M18

- Color: Red food-grade CE certification
- Matter: Silicone
- Shore Hardness: SH60



Variant reference:

92 20SLT M18

- Color: Translucent
- CE food certified
- Matter: Silicone
- Shore Hardness: SH60

Material guide:

	Material	Code	Temperature resistance (°C)	Flexibility	Abrasion resistance	UV/Weather resistance	Oil resistance	Food compatibility	Migration test
	Nitrile Black (Shore SH70)	NI	-10/+80	✓	✓	✗	✓✓	✗	✗
	Silicone Red food-grade CE certification (Shore SH60)	SL	-60/+250	✓✓✓	✗	✓✓✓	✗	FDA  **	A, B, D2
	Silicone Translucent (Shore SH60)	SL T	-60/+250	✓✓✓	✓	✓✓✓	✓	FDA  **	✗

Requests for FDA and/or EC certificates must be made AT THE TIME OF ORDER. Any later request will incur additional charges. To meet the expectations of our industrial customers, NOVACOM offers the widest range of elastomer and thermoplastic materials. We can also develop new materials based on precise specifications, in order to solve specific applications for our customers.



Excellent |



Good |



Low |



Poor |




Not recommended

*FDA and/or EC certificate may be requested for various references at the time of order; please contact us.

** Food contact certification: (EC) 1935/2004 - (FDA) 21 CFR 177.2600

*** Food contact certification: (EC) 10/2011 - (FDA) 21 CFR

Related products:



Bellows Suction Cup 4.5 folds Series 92, Ø 20 mm

Product reference: 92 20-- A



Inner Reinforcement Ring - OD 17.5 mm

Product reference: A20



Check Valve for Fitting 9P18A

Product reference: PAL 9P18A



Rivet for Fitting 9P18A - Aluminium

Product reference: 9P18A RIV